

## Specifications

Item	Standard	Optional
Microprocessor	P54CSLM 133-/150-MHz Pentium® processor	
Main memory	EDO (TSOP) 8MB or 16MB 64-bit memory banks	Expandable to 40MB or 48MB using 8, 16 and 32MB EDO DIMMs
Flash ROM BIOS	256KB, shadow RAM supported	
Data storage devices	Removable 12.7mm, 2.5-inch, 1.44GB or 2.1GB Enhanced-IDE hard disk drive  Internal 3.5-inch, 1.44MB floppy drive	External 15mm, 5.25-inch high-speed CD-ROM drive
Display	DSTN, 800x600, 256 colors (SVGA)	Up to 1024x768, 256-color ultra-VGA monitor LCD projection panel
Video	PCI local bus video with graphics accelerator  1MB video RAM	
Audio	16-bit stereo audio Sound Blaster Pro compatible  Built-in speaker	

Item	Standard	Optional
Keyboard and pointing device	82-/83-key with Windows 95 keys  Touchpad (centrally-located on palmrest)	101-/102-key, PS/2-compatible keyboard or 17-key numeric keypad  External serial or PS/2 mouse or similar pointing device
I/O ports	One 9-pin RS-232 serial port (16550-compatible)  One 25-pin parallel port (ECP-compliant)  One 15-pin CRT port  One 6-pin PS/2 keypad/keyboard/mouse connector  One type III or two type II PC card slot(s)	Serial mouse, printer or other serial devices  Parallel printer or other parallel devices  Up to a 1024x768, 256-color ultra-VGA monitor  17-key numeric keypad, PS/2 keyboard or mouse  LAN card or other PC cards
I/O ports (continued)	Three 3.5mm minijacks for mic-in line-in line-out audio devices	Microphone Audio CD player or Walkman Speakers or headphones
Operating system	Windows 95	
Weight	(includes battery) 2.61 kg. (5.74 lbs.)	
Dimensions (main footprint)	W x D x H 297mm x 219.5mm x 48mm (11.7" x 8.64" x 1.89")	

Item	Standard	Optional
Temperature Operating Non-operating	10°C ~ 35°C -20°C ~ 60°C	
Humidity Operating Non-operating	(non-condensing) 20% ~ 80% 20% ~ 80%	
AC adapter	100~240 Vac, 50~60 Hz autosensing AC adapter	Extra AC adapter
Battery pack  Charge time	Nickel Metal-Hydride battery  2 hr. (rapid charge) 5 hr. (charge-in-use)	Extra battery pack