

Specifications

Item	Standard	Optional
Microprocessor	Intel Pentium™ processor (100/120/133 MHz)	
System memory	8MB / 16MB Dual 64-bit memory banks	Expandable to 64MB using 8, 16 and 32MB ¹ SO DIMMs
Flash ROM BIOS	256KB	
Data storage devices	Removable 12.5mm, 2.5-inch, 810MB Enhanced-IDE hard disk drive Internal 3.5-inch, 1.44MB diskette drive or Internal 17mm, 5.25-inch six-speed CD-ROM drive	1 ⁺ GB Enhanced-IDE hard disk drive External 3.5-inch, 1.44MB diskette drive
Display	DualScan STN or TFT active matrix, 800x600, 256 colors (SVGA)	Up to 1024x768, 256-color ultra-VGA monitor LCD projection panel
Video	PCI local bus video with graphics accelerator 1MB video RAM	

¹ You can upgrade memory using 32MB SO DIMMs when they become available. Consult your dealer for details.

Item	Standard	Optional
Audio	16-bit stereo audio; Built-in dual speakers; separate audio ports	
Keyboard and pointing device	84-/85-/88-key with Windows 95 keys Touchpad (centrally-located on palmrest)	101-/102-key, PS/2-compatible keyboard or 17-key numeric keypad External serial or PS/2 mouse or similar pointing device
I/O ports	One 9-pin RS-232 serial port (16550-compatible) One 25-pin parallel port (EPP/ECP-compliant) One 15-pin CRT port One 6-pin PS/2 keypad/keyboard/mouse connector One type III or two type II slot(s) with ZV port support One external FDD port One 3.5mm minijack audio port for mic-in One 3.5mm minijack audio port for line-in One 3.5mm minijack audio port for line-out	Serial mouse, printer or other serial devices Parallel printer or other parallel devices Up to a 1024x768, 256-color ultra-VGA monitor 17-key numeric keypad, PS/2 keyboard or mouse LAN card or other PC cards External diskette drive Microphone Audio CD player or other line-in devices Speakers or headphones

Item	Standard	Optional
Operating system	Windows 95	Windows NT, OS/2 Warp
Weight FDD CD-ROM	(includes battery) 2.5 kg. (5.5 lbs.) 2.7 kg. (5.7 lbs.)	
Dimensions (main footprint)	W x D x H 306mm x 228mm x 46mm (12.05" x 8.98" x 1.81")	
Temperature Operating Non-operating	10°C ~ 35°C -20°C ~ 60°C	
Humidity Operating Non-operating	(non-condensing) 20% ~ 80% 20% ~ 80%	
AC adapter	100~240 Vac, 50~60 Hz autosensing AC adapter	Extra AC adapter
Battery pack Charge time	Lithium-Ion or Nickel Metal-Hydride smart battery 2-hr. (rapid-charge) 6~8-hr. (charge-in-use)	Extra battery pack External battery charger/discharger