

Specifications

Item	Standard	Optional
Microprocessor	DX4-75 or 5x86-100 processor	
System memory	4MB / 8MB	Expandable to 32MB
CMOS RAM	128 bytes, battery backup	
Data storage devices	One 2.5-inch removable hard disk drive (12.7mm) One 3.5-inch, 1.44MB removable diskette drive	Higher-capacity hard disk drive
Video	1MB video RAM, local bus video with graphics accelerator	
Video display ¹ STN color TFT color	10.4-inch DualScan STN, 640 x 480, 64K colors / 10.4-inch DualScan STN 800 x 600, 256 colors 10.2-inch TFT, 640 x 480, 64K colors	Up to 1024 x 768, 16-color ultra-VGA monitor LCD projection panel
Keyboard	82-/83-/87-key	101-/102-key, PS/2-compatible keyboard or 17-key numeric keypad
Pointing device	Touchpad	

¹ LCD display configurations may differ from area to area.

Item	Standard	Optional
I/O ports	One 9-pin serial port (RS-232) One 25-pin parallel port (EPP/ECP-compliant) One 15-pin CRT port One 6-pin PS/2 keypad/keyboard/mouse connector One PCMCIA type II slot SIR (serial infrared) port (IrDA-compliant)	Serial mouse, printer or other serial devices Parallel printer or other parallel devices Up to a 1024 x 768 ultra-VGA monitor 17-key numeric keypad, PS/2 keyboard, mouse or trackball Fax/data modem card or other PC cards / PCMCIA type III module External IR adapter
AC adapter	100~240Vac, 50~60Hz autosensing AC adapter	Extra AC adapter
Battery pack	NiMH with thermal protection; 2 hours rapid recharge time	Extra NiMH primary battery or secondary Li-Ion battery (available 4 th quarter 1995) External battery charger
Operating system	MS-DOS, Windows	OS/2, Windows NT
Weight (system unit + battery)	2.3 kg (around 5 lbs)	
Dimensions (system unit + battery) STN color TFT color	W x D x H 297mm x 208mm x 42mm 297mm x 208mm x 44mm	Carrying bags
Temperature Operating Non-operating	10°C ~ 35°C 0°C ~ 60°C	
Humidity Operating Non-operating	(non-condensing) 20% ~ 80% 20% ~ 80%	

