

Specifications

Item	Standard	Optional
Microprocessor	Intel Pentium™ processor (running at 75/90 MHz)	
System memory	8MB	Expandable to 40MB
Secondary cache memory	256KB	
ROM BIOS	256KB	
Data storage devices	One 2.5-inch, 340MB removable enhanced-IDE hard disk drive One 3.5-inch, 1.44MB removable diskette drive	510MB or higher capacity hard disk drive module Removable IDE CD-ROM drive module
Video display STN color TFT color	10.4-inch DualScan STN, 640x480, 64K colors (VGA) / 10.4-inch DualScan STN 800x600, 256 colors (SVGA) 10.4-inch TFT, 640x480, 64K colors (VGA) / 10.4-inch TFT, 800x600, 256 colors (SVGA)	Up to 1024x768, 16-color ultra-VGA monitor LCD projection panel

Item	Standard	Optional
Audio/Video	1MB video RAM, 32-bit PCI local bus video with graphics accelerator 16-bit stereo audio, Built-in microphone and speaker	
Keyboard	82-/83-/87-key	101-/102-key, PS/2- compatible keyboard or 17-key numeric keypad
Pointing device	Trackpad	
I/O ports	One 9-pin serial port (RS-232) One 25-pin parallel port (EPP/ECP-compliant) One 15-pin CRT port One 6-pin PS/2 keypad/ keyboard/mouse connector One 240-pin expansion connector One PCMCIA type III or two type II slot(s) SIR (serial infrared) port (IrDA-compliant) Audio port for microphone-in Audio port for line-in Audio port for line-out	Serial mouse, printer or other serial devices Parallel printer or other parallel devices Up to a 1024x768 ultra-VGA monitor 17-key numeric keypad, PS/2 keyboard, mouse or trackball Docking station or port replicator Fax/data modem card or other PC cards External IR adapter Microphone line-in device speakers or headphones

Item	Standard	Optional
AC adapter	100~240Vac, 50~60Hz autosensing AC adapter (+ extender module)	Extra AC adapter (+ extender module)
Battery pack	NiMH with thermal protection and battery gauge; 2.0 hours maximum recharge time	Extra NiMH battery pack, 9-cell/6-cell(+extender module) Li-Ion battery pack (available 4 th quarter 1995) External battery charger
Operating system	MS-DOS, Windows	OS/2, Windows NT
Weight (system unit) w/ battery pack w/ CD-ROM module	2.9 kg (6.4 lbs) 3.15 kg (6.95 lbs)	
Dimensions (system unit)	L x W x H 297mm x 225mm x 48mm (11.7" x 8.86" x 1.9")	Carrying bags
Temperature Operating Non-operating	10°C ~ 35°C -10°C ~ 60°C	
Humidity Operating Non-operating	(non-condensing) 20% ~ 80% 20% ~ 80%	