

Specifications

Item	Standard	Optional
Microprocessor	Mobile Intel Pentium™ processor (133/150MHz)	
Memory System / Main	16MB Dual 64-bit memory banks	Expandable to 64MB using 8/16/32MB soDIMMs
External cache	256KB L2 cache (synchronous SRAM)	512KB L2 cache
FLASH BIOS	256KB	
Storage system	One 2.5-inch, high-capacity Enhanced-IDE hard disk One high-speed IDE CD-ROM drive module One 3.5-inch, 1.44MB floppy drive module (internal/external use)	Higher-capacity E-IDE hard disk
Display	DualScan STN or active-matrix TFT LCD, 800x600, 64K colors (SVGA)	Up to 1024x768, 256-color ultra-VGA monitor LCD projection panel
Video system	PCI local bus video with 128-bit graphics accelerator	

Item	Standard	Optional
Audio system	16-bit stereo audio with built-in FM synthesizer Built-in microphone and dual angled speakers	
Communications system ¹	Built-in V.34 fax/data modem (28.8Kbps) with digital simultaneous voice over data (DSVD) support	PC card modem
Operating system	Windows 95	DOS and Windows 3.x, OS/2 Warp
Keyboard and pointing device	84-/85-key with Win95 keys; auto-tilt feature Touchpad (centrally-located on palm rest)	101-/102-key, PS/2-compatible keyboard or 17-key numeric keypad External serial or PS/2 mouse or similar pointing device
I/O ports	One 9-pin RS-232 serial port (UART16550-compatible) One 25-pin parallel port (EPP/ECP-compliant) One 15-pin CRT port One 6-pin PS/2 connector One 240-pin mini dock connector	Serial mouse, printer or other serial devices Parallel printer or other parallel devices; floppy drive module (when used externally) Up to a 1024x768 ultra-VGA monitor 17-key numeric keypad, PS/2 keyboard, mouse or trackball Mini dock

¹ This feature is available only in the U.S.

Item	Standard	Optional
I/O ports (continued)	One type III or two type II PC Card slot(s) One serial infrared port (IrDA-compliant) One 3.5mm minijack microphone-in/line-in port One 3.5mm minijack speaker-out/line-out port RJ11 phone jack ¹	LAN card or other PC cards External IR adapter Microphone or line-in device Speakers or headphones
Weight with FDD with CD-ROM	(includes battery) 3.4 kg. (7.4 lbs.) 3.5 kg. (7.7 lbs.)	
Dimensions Round contour Main footprint	L x W x H 297~313 x 230~240 x 48~53 mm 11.7 x 9.1 x 2 inches	Carrying bag
Temperature Operating Non-operating	10°C ~ 35°C -10°C ~ 60°C	
Humidity Operating Non-operating	(non-condensing) 20% ~ 80% RH 20% ~ 80% RH	

¹ This option is available only in the U.S. and Japan.

Item	Standard	Optional
AC adapter	100~240Vac, 50~60Hz autosensing AC adapter	Extra AC adapter
Battery pack Type	57WH Lithium-Ion battery with intelligent charging and built-in battery gauge	Extra battery pack
Charge time	2.0-hour rapid-charge 4.0-hour charge-in-use	